Exhibit A

SOUTHERN CLAY PRODUCTS / A SUBSIDIARY OF ROCKWOOD SPECIALTIES, INC.

PRODUCT BULLETIN/Laponite®



Southern Clay Products, Inc. 1212 Church Street Gonzales, TX 78629 Phone: 800-324-2891 Fax: 830-672-1903 www.scprod.com

Laponite B

MARKET STATE OF THE STATE OF TH

The Clear Leader

Description

LAPONITE B is a synthetic layered fluorosilicate. It is insoluble in water but hydrates and swells to give translucent, colorless colloidal dispersions. At 2% concentration in water, highly thixotropic gels are obtained.

Application

Used for imparting shear sensitive structure to waterborne formulations.

Typical Characteristic

•	Chemical Composition	(dry basis)
Appearance free flowing white powder	SiO ₂	55.0%
Bulk Density 1000 kg/m3	MgO	27.0%
Surface Area (BET) 330 m2/g	Li ₂ O	1.4%
pH (2% suspension) 9.4	Na ₂ O	3.8%
	F	5.6%
	Loss on Igr	nition 7.2%

General Specifications

Rockwood QA Test Code

Gel strength 15g min ELP-L-1D
Sieve Analysis 1% Max >250 microns ELP-L-6A
Free Moisture 10% Max ELP-L-5A
Specifications can be agreed to meet individual requirements.





Storage

Laponite is hygroscopic and should be stored under dry conditions.

For additional information or technical assistance contact Southern Clay Products, Inc. toll free at 800-324-2891.

Disclaimer of Warranty: The information presented herein is believed to be accurate but is not to be taken as a warranty, guarantee, or representation for which we assume legal responsibility. This information does not grant permission, license, or any rights or recommendations to practice any form of proprietary intellectual property without obtaining the appropriate license or grant from the property owner. The information is offered solely for your consideration, investigation and verification, but you must determine the suitability of the product for your specific application. The purchaser assumes all risk of use of handling the material, including but not limited to transferring the material within purchaser's facilities, using the material in applications specified by the purchaser and handling any product which includes the material, whether or not in accordance with any statements made herein.